

VICINAY CADENAS, S.A.

B I L B A O

SYNTHESIS REPORT
Project: Brite 5309 "QWELD"

BRE2 - 0195

September 96

Synthesis Report

1. QWELD PROJECT OBJECTIVES

As described in 1992, the basic objectives of the Qweld project were as follows:

- 1 Achieve a level of quality assurance in the production of welded products, and in particular links of chain welded using the *Flash butt welding system*, which would mean that not all of the weld inspections would have to be performed.
- 2 Reduce quality costs from 16% to 6% including industrial problems like defects, rejects, repairs, recoveries, unnecessary inspection times, queues of products with processing unfinished because they are in intermediate processes, warehouse surpluses, etc.
- 3 Reduce chain weight by 15% to enable the manufacturer to produce these goods with material weighing 1.00Mpas when the current standards reach 860' Mpas.
- 4 Develop a theoretical and scientific quality control system that enables the manufacturer to control 20 parameters of the welding process in 'real time.'
- 5 Enable the gathering and management of information in a highly polluted industrial environment, particularly electromagnetic and solid particle pollution;
- 6 Incorporate in each individual manufacturing phase data coming from the raw material, heat treatment, load tests, etc.
- 7 Full traceability in the products "mentioned to each individual manufacturing phase of the industrial high-tech chain process."
- 8 Lay the foundations for a standard or, at least, a pre-standard applicable to manufacture and placement on the high-tech chain market.

Success of each phase measured in ascending order from 1 to 10.

2 COMPARISON OF ORIGINAL FEATURES AND OBJECTIVES ACHIEVED

Of the above points, the following has been achieved:

1 Reduction to a level lower than 100% of link inspections

This was not achieved as the cases of potential defects in links makes it **unadvisable**.

Even so, the capacity to recognise in real time many of the links that may be defective was achieved. Such identification is estimated at 80% of all cases. Coverage: 8.

2 Reduce quality costs from 16% to 6 %

The figure of 6% was studied in great detail, and it soon became clear that it was not a realistic target, as not even firms with the highest quality levels in the world achieve it. In the case of Vicinay Cadenas, the figure was reduced from 16% to 12%, giving a coverage level of: 7.

3 Reduce chain weights by up to 15%

As a consequence of the project, chains of 1000Mpa were achieved and an alternative product known as VGW was also developed. Between the two, chain weights are being reduced by up to 30%.

The project has given rise to a new product project known as UCL which aims to reduce chain weight by up to 60%. Coverage: 9.

4 Do the theoretical and scientific groundwork required to handle 20 parameters of the weld process in real time

Up to 30 parameters were controlled and managed, some of them with a read-off frequency of one reading per 10 milliseconds. Coverage: 8.

5 Work in an industrial environment

Work was carried out in highly-polluted industrial environments, with electromagnetic and dust pollution produced by the solidification of liquids and metal vapour emitted during the welding process.

Seii has also been able to apply Qweld project technology to gathering environmental information to control critical parameters in large cities, and in, among others, the oil, petrochemical, chemical and metal industries. Coverage: 8.”

6 Incorporate each industrial phase of the welding process from raw material to treatment and load testing

By the end of the project, a system had been developed to predict the mechanical properties of the materials according to the chain manufacture and heat treatment parameters.

A new project called *QHeat* was developed. In the new project, the heat treatment system is subjected to controls as accurate and rigorous as those in *Qweld*.

A non-destructive, ultrasound inspection system, known as *Quse*, was also developed. Here all the information is computerised and related to the individual links developed with full traceability in *Qweld*.

In this heading, the project was essential to progress in chain manufacturing technology. Coverage: 8.

7 Ensure full traceability for each individual phase of the links

The traceability required was achieved by incorporating all the relative movements of position of the links throughout the industrial process.

This fact is particularly relevant bearing in mind that the links do not have individual identification **using** bar or alphanumerical codes. Nevertheless, with the current system, the Traceability safety level is 70%, which increases to 95% with manual aid.

This is one feature being improved in the following phase of the project which Vicinay Cadenas has just contracted out to the Labein Technology Centre in Bilbao. Coverage 7.

8 Development of standards for manufacture and use of high-tech chains in the offshore industry

Det Norske Veritas has developed a standard known as CN:6 which came into effect for the whole high-tech chain market in July 1996. Coverage: 8.

In view of these results, the project can be considered a complete success from the scientific point of view, although the parties acknowledge that industrial development for its market placement is rather less advanced in the areas of welding. However, it has provided exceptional grounding for its application in other industrial areas such as the environment.

3. RESOURCES

To achieve the objectives mentioned at the beginning, neither of the main contractors, i.e., Vicinay Cadenas, S.A. and Seii (with between them more than 90% of the responsibility for the project), have spared either human or technological resources.

The fact is that Seii suffered severe economic problems that led to the company being declared bankrupt. The new owners of the firm, the *Fournie-Grospand* group, made an enormous effort, actually taking the risky decision to commit part of the future of the new company to

satisfying in, full the previously-acquired commitments of the original firm.

Vicinay Cadenas also made a remarkable effort, with 4 staff members giving 100% of their time to the project throughout the 3 and a half years of its duration.

Vicinay Cadenas also acquired the computer equipment it needed to make a prototype unit and spread knowledge and application to the industrial units.

The extension of the application to the industrial world threw up stiff resistance, which has compelled the firm to prolong the project, internally at least, for a further year. In this case, the extension is being performed under an agreement signed, with the Labein technology centre in August 1996.

4. CONCLUSIONS

The project can be considered reasonably successful. As mentioned earlier, the main objectives were achieved, some to as much as 90%, with others to a lower, although still highly significant, percentage.

The main contractors, Vicinay Cadenas and Seii, have both improved their positions in their specific markets, thanks to the performances achieved in the project.

The former because it has gained status as a leader on the world high-tech chain market, through having been the undisputed champion of *new* products such as:

- Studless chains and **VGW** chains.
- Development of **UCL** chains, a new, potentially revolutionary product which should be out on the market by 1999.

- Vicinay has also taken advantage of the **technological and development** know-how **thrown up** by the project to start parallel research projects, **such as:**
 - Fatigue on real scale, with the Labein technology centre
 - *Qheat*, for the control and traceability of continuous heat treatments, run by Vicinay staff
 - *Quse*, for computerisation and digital treatment of nondestructive, particularly ultrasound, test inspections

As a consequence of the Qweld project, information from all these projects can be threaded and then linked to an individual component, thereby providing a history of all the significant events in the production cycle of the individual product in question, beginning with the raw materials and ending with the final part of the manufacturing process.

5. ACKNOWLEDGEMENTS



Qweld project management would like to thank all the members of the project for their efforts, dedication and interest. A good, cooperative working environment was created between everyone involved, proving vital to the success of the project, the achievement of the objectives and the results presented herein.

6. TABLES

Diagrams of the most significant parts of the Qweld, Qheat and Fatiga project—all of them linked in the Master Qweld project—are attached.

Maquina 1 Fecha 15.96 Sublargo 540972 46126.00

Presion de recaldo





NUMERO_DE_ESLABON

VI CADENAS SA

(SE |-| SEI)

Tension primaria




NUMERO_DE_ESLABON

VIC_NAY CADENAS SA


SE - ISE

Velocidad a in de aceleracion

Maquina 1 = Fecha fab 7 5 96 - Sublargo 6 40972 4 6 126 00




Presión de cierre o fuerza



Uni.: Kg/cm²

Nmax: 111.75
Nmin: 110.46
R: 0.21
med.: 110.68
desv.: 0.927362





VICINAY CADENAS SA

NUMERO_DE_SLABON

(SE - S≤

Recorrido de reca cad.



Maquina 1 - Fecha fab 7.5.96 - Sublargo 6 40972 4 6 126.00





V CINAY CADENAS SA

S&I

Tiempo de soldadura







Honeywell 30-Sep-96 08:30:05

Alarm

Fire

Vicinay

Stn01 Oper Pg 611

HORNOS DE REYEMBO


constante TEMPERATURA

Zona 1
Zona 2
Zona 3
Zona 4
Zona 5
Zona 6
Zona 7

Presión PAA

GAS → 0 %

0 % → GAS




Registro 15 HORNO TEMPLE.CONTROL

Visualización Multiesc. | Muestras | 1000 Intervalo 8 horas |



1315.000



EU

HT1TIC1

00000000

Nombre	Parámetro	Nombre PV	Nombre CO	Rango Variable	Valor actual
HT1TIC1		PV	CONTROL TEMPERATURA ZONA 1	00000000 - 10000000	840 GRADOS
HT1TIC2		PV	CONTROL TEMPERATURA ZONA 2	00000000 - 10000000	840 GRADOS
HT1TIC3		PV	CONTROL TEMPERATURA ZONA 3	00000000 - 10000000	940 GRADOS
HT1TIC4		PV	CONTROL TEMPERATURA ZONA 4	00000000 - 10000000	939 GRADOS
HT1TIC5		PV	CONTROL TEMPERATURA ZONA 5	00000000 - 10000000	920 GRADOS
HT1TIC6		PV	TEMPERATURA LUMENES	00000000 - 10000000	
HT1TIC7		PV	TEMPERATURA LUMENES	00000000 - 10000000	

Now

26.000

Last 1000 Data

Fecha 3 / 7 / 96

Consignas Temple ±10

Consignas Revenido ±10

Diam Grado Ord Fabricacion

120.0 R3 41103

0.0

0.0

Temperatura de Tratamiento (grados)

TAqua=37 ±7 Velocidad ±5% 165

Tiempos Largos OFER Veloc T.

hh min. ENTR MANDO mm/min. Ag

Zona de Temperatura

Hogar de Revenido

Z1 Z2 Z3 Z4 Z5 Z1 Z2 Z3 Z4 Z5 Z6

6 0 BL 8 Manicu 165 33

839

840

940

935

920

558

607

649

644

645

645

840

840

940

935

920

568

607

650

645

645

645

840

840

940

938

920

557

606

650

644

645

645

840

840

940

939

920

560

606

651

646

645

644

840

840

940

940

920

575

609

651

648

645

638

840

840

940

941

920

566

597

647

650

640

628

840

840

940

940

920

559

580

655

647

642

650

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

559

580

655

647

642

650

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940

920

549

567

650

645

644

647

840

840

940

940